



Addressable Panic Button

Stainless Steel button with LED



L7322

Shown mounted in surface back-box available separately

Product Description

The Addressable Panic Button provides a robust, reliable, simple to use unit for use in harsh environments such as prisons, courts, hospitals etc. The system is made up from **Call Points** (Shown above) located throughout the establishment where a Panic Call may be required and **Liquid Crystal Display Units**, which show the location of any Calls and sound the alarm. Additional sounders and output(s) can be configured on the system to activate for specific Code Blue call points or sensitive areas.

L7322 Call Points

The Code Blue Call Point comprises: Stainless Steel Panel, call button with integral red re-assurance LED and protective shroud to prevent accidental or inadvertent activation. All units are fitted with a tamper device, which indicates on the LCD as a separate alarm in the event that the unit is removed from the wall or back box. Each call point has a corresponding text location, programmed into the system during the commissioning process which can be altered at any time in the future. All text descriptions are held in flash memory to prevent corruption in the event of a power failure. The unit is manufactured from robust 1.5mm stainless steel and supplied with two stainless steel tamper resistant fixings.

Programmable Call Type & Auxiliary Connections

The L7322 unit can be programmed to generate differing levels of call, available options are; Call, Assist, Emergency, Attack, Call (Remote Reset) and Assist (Remote Reset). Each call type integrates with the standard range of Intercall 600/700 product ranges. The generated call type is indicated by the integral red re-assurance LED. The unit features external input connection which also can be programmed to various call types including reset and an external LED drive output.

LCD Displays

The Calls are available in stainless steel or plastic enclosures depending upon the environment. They comprise: two line 32 character Liquid Crystal Display with backlight accept button and integral adjustable alarm.

System Description

The system is fully addressable and up to 254 Call Points can be connected to a single system. All network components are connected to a common two-wire bus, making installation and fault finding very straightforward. The units can be integrated into the Intercall 600 or Intercall 700 Nursecall system so and system activity can be collected and analysed using the Call Management Software.